

PACKED WITH
POSSIBILITIES.



20TB



20,000 LBS



AVAILABLE
BED LENGTH

20' - 30'



STANDARD
WINCH

8,000 LBS

NRC 


NRC-INDUSTRIES.COM

CARRIER

20TB

Every adventurer needs a trustworthy sidekick, and we took the liberty of making just that. Roadside assistance, recovery, transport - the 20TB carrier is here and ready for anything. The best features for the best performance.

Haul all you can think of, and then some. It's all in a days work. Thanks to its great reliability and versatility, the 20TB series allows you to increase revenue while considerably reducing your maintenance costs.



CARRIER SPECIFICATIONS

- Tow bar lift rating: 8,000 lbs @ 0" / 3,000 lbs @ 48"
- Operating pressure: 2,600 psi
- Tow rating : 15,000 lbs
- Deck width : 102"

STANDARD EQUIPMENT

- Standard winch: 8,000 lbs
- Dual controls - lever type
- Pressure gauge
- Independant hydraulic tow bar
- Wheel lift system
- Fixed headboard with chain rack (winch embedded in chain rack)
- 3 marker lights & 3 chain slots per side
- Hydraulic oil tank with filter - 12 GAL
- Hydraulic gear pump, direct mount - 17 GPM

MINIMUM FRAME REQUIREMENTS

- Cab to axle (single): 144" - 244"
- Cab to axle (tandem): 196" - 274"
- Minimum RBM for 21'-25': 1,250,000 lbs*in / rail
- Minimum RBM for > 25': 1,925,000 lbs*in /rail
- Minimum RBM for tandem: 2,250,000 lbs*in / rail

DEALER:

NRC 

NRC-INDUSTRIES.COM

Tel: 450 379-5796 | Fax: 450 379-5995