

PACKED WITH
POSSIBILITIES.



20TB



20,000 LB



20' to 30'



8,000 LB



CARRIER

20TB

Built for operators who do it all, the 20TB carrier is a dependable partner for roadside assistance, recovery, and transport. Its versatile design allows it to adapt to changing terrain and job requirements with ease. Featuring proven components and smart engineering, the 20TB delivers strong performance, smooth operation, and excellent reliability. Designed to maximize uptime, it helps increase revenue while significantly reducing maintenance costs over the long run.



CARRIER SPECIFICATIONS

- Tow bar lift rating: 8,000 lb @ 0" / 3,000 lb @ 48"
- Operating pressure: 2,500 psi
- Tow rating: 15,000 lb
- Deck width: 102"

STANDARD FEATURES

- Standard winch: 8,000 lb
- Dual controls - lever type
- Pressure gauge
- Independent hydraulic tow bar
- Wheel lift system
- Fixed headboard with chain rack (winch embedded in chain rack)
- 5 marker lights & 3 chain slots per side
- Hydraulic oil tank with filter - 13 gal
- Hydraulic gear pump, direct mount - 17 gpm

CHASSIS REQUIREMENTS

- Cab to axle (single): 144" - 244"
- Cab to last axle (tandem): 196" - 274"
- Minimum RBM for 21' - 25': 1,250,000 in-lb per rail
- Minimum RBM for > 25': 1,925,000 in-lb per rail
- Minimum RBM for tandem: 2,250,000 in-lb per rail

AUTHORIZED DEALER:



Scan
to learn
more.

NRC

[NRC-INDUSTRIES.COM](https://www.nrc-industries.com)

450 379-5796

Rev. 2026-03