

WHERE THE WORK
HAPPENS.



30CS



30 TONS



30,000 LB



168"



WRECKER

30CS

Built for the realities of day-to-day recovery, the 30CS strikes the perfect balance between compact size and reliable strength. Its well-thought-out layout and proven components make it ideal for roadside assistance, light to medium recovery, and tight urban environments. Designed with NRC's focus on durability and operator efficiency, the 30CS is easy to operate, simple to maintain, and ready to perform—shift after shift.



WRECKER SPECIFICATIONS

- 30-ton rated lifting capacity
- Dual 30,000 lb 2-speed planetary winches
- Working hydraulic pressure: 3,000 psi
- Composite body 102" wide (including fenders)

BOOM SPECIFICATIONS

- Slider® system offering 97" of sliding travel
- 2-stage telescopic high-tensile multi-fold boom
- Structural rating fully retracted: 60,000 lb (30° SAE J2512)
- Structural rating fully extended: 25,000 lb (30° SAE J2512)
- Reach past tailgate: 168"
- Maximum working height: 306"
- Range of elevation: 0° - 64°
- 360° sheave head

CHASSIS REQUIREMENTS

- Front axle: minimum 14,600 lb capacity
- Rear axle: minimum 40,000 lb capacity
- Minimum frame RBM: 3,250,000 in-lb per rail
- Minimum CLA required: 183"

AUTHORIZED DEALER:



Scan
to learn
more.

NRC 

NRC-INDUSTRIES.COM

450 379-5796

Rev. 2026-03