

**POWER AND  
VERSATILITY  
COMBINED.**



# 40CS



40 TONS



40,000 LB



279"



## WRECKER

# 40CS

The 40CS is built for operators who want more capability without unnecessary complexity. With increased lifting capacity, extended reach, and a rugged structural design, it takes on tougher recoveries with confidence. From routine roadside calls to more demanding recovery jobs, the 40CS offers smooth operation, dependable performance, and long-term durability—everything operators expect from NRC equipment.



### WRECKER SPECIFICATIONS

- 40-ton rated lifting capacity
- Working hydraulic pressure: 3,000 psi
- Dual 40,000 lb 2-speed planetary winches
- Composite body 102" wide (including fenders)

### BOOM SPECIFICATIONS

- Slider® system offering 97" of sliding travel
- 2-stage telescopic high-tensile multi-fold boom
- Optional 3-stage version
- Structural rating fully retracted: 80,000 lb (30° SAE J2512)
- Structural rating fully extended (2-stage): 30,000 lb (30° SAE J2512)
- Structural rating fully extended (3-stage): 15,000 lb (30° SAE J2512)
- Reach past tailgate: 188" (2-stage), 279" (3-stage)
- Maximum working height: 332" (2-stage), 410" (3-stage)
- Range of elevation: 0° - 59°
- 360° sheave head

### CHASSIS REQUIREMENTS

- Front axle: minimum 18,000 lb capacity
- Rear axle: minimum 40,000 lb capacity
- Minimum frame RBM: 3,250,000 in-lb per rail
- Minimum CLA 183" for tandem axle body (from cab to center of rearmost axle)
- Minimum CLA 201" for tri-axle body (from cab to center of rearmost axle)

**AUTHORIZED DEALER:**



Scan  
to learn  
more.

**NRC** 

**NRC-INDUSTRIES.COM**

450 379-5796

Rev. 2026-03