

A NEW LEVEL OF
PERFORMANCE
AND **CAPABILITY.**



40TB



40,000 LB



24' to 30'



20,000 LB



CARRIER

40TB

Designed to handle heavy transport applications, the 40TB carrier combines high load capacity with NRC's proven durability and smart engineering. Its reinforced deck beams, rigid cross-members and oversized subframe components push the limit of what a carrier can haul in a day, every single day. Whether transporting heavy equipment or managing challenging recovery scenarios, the 40TB delivers consistent performance, excellent control, and long-term reliability.



CARRIER SPECIFICATIONS

- Tow bar lift rating: 20,000 lb @ 0" / 10,000 lb @ 58"
- Operating pressure: 2,800 psi
- Tow rating: 50,000 lb
- Deck width: 102"

STANDARD FEATURES

- Standard winch: 20,000 lb
- Dual controls - lever type
- Pressure gauge
- Independent hydraulic tow bar
- Wheel lift system
- Fixed headboard with chain rack (winch embedded in chain rack)
- 55 marker lights & 5 chain slots per side
- Hydraulic oil tank with filter - 13 gal
- Hydraulic gear pump, direct mount - 17 gpm

CHASSIS REQUIREMENTS

- Cab to last axle: 196" - 274"
- Minimum RBM for tandem: 2,500,000 in-lb per rail

AUTHORIZED DEALER:



Scan
to learn
more.

NRC 

NRC-INDUSTRIES.COM

450 379-5796

Rev. 2026-03