

SEIZE MORE
OPPORTUNITIES.



50CS



50 TONS



50,000 LB



280"



WRECKER

50CS

Designed to handle tougher recovery scenarios, the 50CS delivers increased lifting power and enhanced stability where it matters most. Its reinforced structure and optimized hydraulics provide the confidence to manage complex recoveries with control and precision. Built around operator efficiency and durability, the 50CS combines strength and responsiveness, making it a dependable tool for demanding recovery work in any environment.



WRECKER SPECIFICATIONS

- 50-ton rated lifting capacity
- Dual 50,000 lb 2-speed planetary winches
- Working hydraulic pressure: 3,000 psi
- Composite body 102" wide (including fenders)

BOOM SPECIFICATIONS

- Slider® system offering 97" of sliding travel
- 2-stage telescopic high-tensile multi-fold boom
- Optional 3-stage version
- Structural rating fully retracted: 100,000 lb (30° SAE J2512)
- Structural rating fully extended (2-stage): 40,000 lb (30° SAE J2512)
- Structural rating fully extended (3-stage): 20,000 lb (30° SAE J2512)
- Reach past tailgate: 189" (2-stage), 280" (3-stage)
- Maximum working height: 333" (2-stage), 410" (3-stage)
- Range of elevation: 0° - 59°
- 360° sheave head

CHASSIS REQUIREMENTS

- Front axle: minimum 18,000 lb capacity
- Rear axle: minimum 46,000 lb capacity
- Minimum frame RBM: 3,250,000 in-lb per rail
- Minimum CLA 183" for tandem axle body (from cab to center of rearmost axle)
- Minimum CLA 201" for tri-axle body (from cab to center of rearmost axle)

AUTHORIZED DEALER:



Scan
to learn
more.

NRC 

NRC-INDUSTRIES.COM

450 379-5796

Rev. 2026-03