

STRONGER.  
SMARTER.  
STEADIER.



# CSR65

  
CAPACITY

65 TONS

  
STANDARD  
WINCHES

50,000 LB

  
BOOM  
REACH

373"

**NRC** 

## WRECKER

# CSR65

At NRC, innovation is an obsession—and the CSR65 proves it. Engineered to exceed expectations, this rotator features the Slider® system to delivers increased lifting power, extended reach, and precise control through advanced technologies and perfectly tuned features. The evolved CSR design includes larger cylinders, a redesigned boom profile, an ergonomic control panel with Lift-IQ™ technology, and wider outriggers with wear pads. The CSR65 doesn't avoid challenges—it takes them head on.



### WRECKER SPECIFICATIONS

- 65-ton rated lifting capacity
- Average body weight: 47,000 lb
- Dual 50,000 lb 2-speed planetary winches
- Composite body 102" wide (including fenders)

### BOOM SPECIFICATIONS

- Slider® system offering 127" of sliding travel and 360° continuous rotation
- 3-stage telescopic high-tensile multi-fold boom
- Structural rating fully retracted: 130,000 lb (30° SAE J2512)
- Structural rating fully extended: 28,000 lb (30° SAE J2512)
- Reach past tailgate: 373"
- Maximum working height: 530"
- Range of elevation: 0° - 70°
- 360° sheave head
- D-rings on each boom sections

### CHASSIS REQUIREMENTS

- Front axle: minimum 20,000 lb capacity
- Rear axle: minimum 66,000 lb capacity
- Minimum frame RBM: 4,500,000 in-lb per rail
- Minimum CLA 246" (from cab to center of rearmost axle)

**AUTHORIZED DEALER:**



Scan  
to learn  
more.

**NRC** 

**NRC-INDUSTRIES.COM**

450 379-5796

Rev. 2026-03