

THE **TOUGHEST**
DETACHABLE UNIT
IN THE INDUSTRY.



QUICKSWAP™



35,000 LB+



UP TO 90,000 LB



FROM 6,500 LB



DETACHABLE UNIT

QUICKSWAP™

Quickswap's tough components and lightweight design make it a true workhorse. Add a winch and use it as a supporting recovery unit. Efficient in every sense of the word, the Quickswap™ saves big on fuel and maintenance costs while maximizing the possibilities... and your profits. Take advantage of the detachable design to push your limits during high seasons, and adapt during slower periods.



QUICKSWAP™ SPECIFICATIONS

- Towing capacity: up to 90,000 lb
- Underlift lifting capacity: 35,000 lb and more
- Detachable from tractor in minutes
- Basic weight: starting at 6,500 lb

STANDARD FEATURES

- 3-stage HD underlift
- Dual cylinders for underlift elevation
- Hydraulic underlift extension, tilt boom and fold
- Removable front stands
- Manual controls
- Safety chain pockets
- Aluminum fenders
- Fork storage and holders
- Tie-down chains

CHASSIS REQUIREMENTS

- Front axle: minimum 12,000 lb capacity
- Rear axle: minimum 40,000 lb capacity
- Minimum frame RBM: 3,250,000 in-lb per rail
- Minimum CLA: 123''

AUTHORIZED DEALER:



Scan
to learn
more.

NRC 

NRC-INDUSTRIES.COM

450 379-5796

Rev. 2026-03