

BUILT TO GET
THE **JOB DONE.**

QUICKSWAP™ WITH INTEGRATED BOOM



25 TONS



78"



FROM 8,750 lb



DETACHABLE UNIT

QUICKSWAP™ WITH INTEGRATED BOOM

This legendary unit is now available with an optional integrated boom, delivering unmatched versatility to the toughest detachable unit in the industry. Designed for operators who demand both exceptional towing performance and true recovery capabilities, the new QuickSwap™ configuration features a two-stage telescopic boom with up to two 25,000 lb planetary winches. Bonus point: zero stress when you hit the scales.



QUICKSWAP™ SPECIFICATIONS

- Towing capacity: up to 90,000 lb
- Underlift lifting capacity: 35,000 lb and more
- Detachable from tractor in minutes
- Basic weight: starting at 8,750 lb

BOOM SPECIFICATIONS

- 2-stage telescopic boom
- Structural rating fully retracted: 50,000 lb (30° SAE J2512)
- Structural rating fully extended: 16,000 lb (30° SAE J2512)
- Reach past tailgate: 78"
- Maximum working height: 180"
- Range of elevation: 15° - 40°

Note: This unit is a standard Quickswap™ equipped with additional optional features — including jack legs, the integrated boom with an underlift arm tilting mechanism (patent pending), and winch options. For the complete list of standard and optional equipment, refer to the Quickswap™.

CHASSIS REQUIREMENTS

- Front axle: minimum 12,000 lb capacity
- Rear axle: minimum 38,000 lb capacity
- Minimum frame RBM: 3,250,000 in-lb per rail
- Minimum CLA: 123"

AUTHORIZED DEALER:



Scan
to learn
more.

NRC

NRC-INDUSTRIES.COM

450 379-5796

Rev. 2026-03